

## Titan<sup>™</sup> Single Brewer



### Features

#### Titan Single Brewer

**High-volume brewing solution that features simple operation, precise extraction control and portable servers**

- Brews up to 22.5 gallons (85.2 litres) of perfect coffee per hour.
- Coffee extraction controlled with pre-infusion and pulse brew, digital temperature control, and large sprayhead; coffee strength controlled with variable by-pass.
- BrewMETER<sup>®</sup> allows automatic programming of pulse routine.
- SplashGard<sup>®</sup> funnel and funnel locks help improve safety.
- Funnel has 28 ounce (.8 kg) ground coffee capacity and paper filter retainers to eliminate fold-over.
- Titan TF servers are insulated to keep coffee hot for hours.
- Hot water faucet.
- 3-Phase or Single-Phase operation.
- Energy-saver mode reduces tank temperature during idle periods.

#### Model Titan Single Brewer with 3 gallon (12 litres) TF Server

*(servers sold separately)*

Dimensions: 40.02" H x 21.3" W x 21.74" D  
(101.7cm H x 54.1cm W x 55.2cm D)

For current specification sheets and other information, go to [www.bunn.com](http://www.bunn.com).

### Related Products

**Easy Clear<sup>®</sup> EQHP-54**  
Product No. : 39000.0006



**Easy Clear<sup>®</sup> EQHP-54L**  
Product No. : 39000.0003

**Titan/Urn Filter Pack**  
Product No. : 20111.0000  
Packed per case: 250  
Dimensions:  
20" Base x 8" Sidewall  
50.8 cm Base x 20.3 cm Sidewall



**Titan TF Server**  
Product No.: 39400.0001  
3 gallon (12 litres)



**Titan Funnel**  
Product No.: 40114.0000



## Dimensions & Specifications

Model	Product #	Volts	Amps	Total Watts	Brewing Capacity	Shipping Weight	Funnel Locks	Cord Attached	Agency
Titan Single	39300.0002	230/400	16	11125	22.5 gal/hr (85.2 l/hr)	107 lbs. (48.5 kg)	Yes	No	CE
		(3-phase)	32.8	7550	17 gal/hr (64.4 l/hr)				
		230*							
		(1-phase)							


**Brewing capacity:** based upon incoming water temp of 15°C (78°C rise).

\*Brewer can easily be rewired in the field for single-phase operation.

Electrical: Brewer is 4-wires plus ground service rated 230/400V, 3-phase, 50/60Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with 3/8" male flare fitting, and back-flow prevention.

4 gal/min (15.2 l/min) requirement. Tank capacity: 9.7 gallons (36.6L)



Bunn-O-Matic® Corporation - 1400 Stevenson Drive Springfield, Illinois 62703 • USA • +1-217-529-6601 • Fax +1-217-529-2827 • www.bunn.com

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

All dimensions shown in centimeters.

12/08 © Bunn-O-Matic Corporation