

Cristallo 600

Cristallo 600 is a completely automatic vending machine with high performance, designed to ensure the best quality espresso and to reduce maintenance and service.

Technologically advanced and extremely user-friendly, it offers up to 16 different beverages.

It is perfectly co-ordinated with Smeraldo 56.



Main features

- Automatically dispenses cups, sugar and stirrers
- Saeco Brewing Unit with the new pre-heating system: top quality espresso from the first dispensing, easy cleaning and maintenance
- Tilting main plate to allow direct access to all the internal components
- Possibility to install 3 payment systems on the door at the same time
- Accepts the most commonly used parallel and serial MDB, BDV and Executive (possible Master and Slave configurations) payment systems
- Easy ordinary maintenance thanks to the 5-button keypad as standard
- Standard CPU for the whole range

- Customisable settings
- High safety for customer and operator

Accessories

- Independent water tank kit
- Timekeeper kit
- Mixer kit for tea spiral replacement with decaffeinated/ barley
- Hot water solenoid valve kit
- 12 V DC validator kit
- Electromechanical pulse counter kit
- Memory key to copy and quickly transfer machine settings
- Eva-Dts 6.0 kit

Ideas with Passion

 **Saeco**



**Cristallo 600 +
Smeraldo 56**

Technical Data	Cristallo 600
Dimensions (w x h x d)	577 x 1830 x 600 mm
Weight	105 kg
Power supply	230 V/50 Hz 220 V/60 Hz 120 V/60 Hz
Power consumption	1250 W
Boiler	brass
Water connection	3/4" (1-8 bar)
Water supply	standard: water supply optional: independent water tank kit
Coffee bean container	1
Instant product container	5
Sugar container	1
Disc mixer	4
Spiral mixer	1
Brewing unit	7 gr or 9 gr
Available cups ø	70 or 73 mm
Available stirrers	90 - 105 - 115 mm
Number of selections	16
Number of preselections	4

Capacities	Cristallo 600
Coffee beans	4.2 kg
Instant coffee	0.8 kg
Milk	2.7 kg
Chocolate	5.4 kg
Tea	3.8 kg
Barley	0.8 kg
Sugar	4.0 kg
Cups (h 70 mm)	550
Stirrers	550
Independent water tank	1 or 2 tanks of 15 l

Technical specifications

- Pre-galvanized and painted steel-sheet body
- Containers and tanks in food-contact approved polypropylene
- Pre-heating system for the brewing unit
- Tilting main plate
- Water, coffee and cup-empty signal
- Stirrer dispenser settable on site
- Electronically controlled boiler temperature
- Exhauster to absorb internal moisture and additional steam exhauster for the dispensing area
- Removable cup-releasing device for easy cleaning and checking
- 60 W electromagnetic vibration pump
- Anti-overflow air-break device
- Simplified error reset
- Boiler safety valve
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- CE, Demko, UL GS and UL approved

User interface

- Direct access 16-button keypad for beverage selection
- 4 preselection keys: +/-sugar and 2 settable keys (decaffeinated/barley, no-cup and only-cup options)
- 2-line, 20-character alphanumeric display



 **FSC** © Mixed Sources
Product group from well-managed forests
and other controlled sources
www.fsc.org Zert.-Nr. GFA-COC-001492
© 1996 Forest Stewardship Council

Saeco Vending S.p.A.

Località Casona, 1066
40041 Gaggio Montano, Bologna - Italy
Tel: +39 0534 7741 - Fax: +39 0534 774808

info.saecovending@saeco.com
www.saeco.com

Always at your service: