

# Rubino 200

Rubino 200 is the completely automatic table-top vending machine of the last generation with design and technical performance at the top of the range. It is specifically designed for small and medium locations.

Available with cabinet in two versions, standard and for payment system, it dispenses up to 8 different beverages.



## Main features

- Automatically dispenses cups (up to 195), sugar and stirrers
- Saeco Brewing Unit: top quality espresso, easy cleaning and maintenance
- Accepts the most commonly used parallel and serial MDB, BDV and Executive (possible Master and Slave configurations) payment systems
- 6 gr to 9 gr adjustable doser
- Updated water circuit
- Standard CPU for the whole range
- Customisable settings
- High safety for customer and operator

## Accessories

- Cabinet with height-adjustable feet (w x h x d 410 x 800 x 537 mm, 24 kg)
- Cabinet with height-adjustable feet suitable for change-giver (w x h x d 410 x 800 x 537 mm, 24 kg)
- Independent water tank kit
- Timekeeper kit
- Mixer kit for tea spiral replacement with decaffeinated/ barley
- 12 V DC validator kit
- Electromechanical pulse counter kit
- 5-button keypad kit
- Memory key to copy and quickly transfer machine settings
- Eva-Dts kit



Technical Data	Rubino 200
Dimensions (w x h x d)	410 x 757 x 537 mm
Weight	46 kg
Power supply	230 V/50 Hz 120 V/60 Hz
Power consumption	1250 W
Boiler	brass
Water connection	3/4" (1-8 bar)
Water supply	standard: water supply optional: independent water tank kit
Coffee bean container	1
Instant product container	3
Sugar container	1
Disc mixer	1
Spiral mixer	1
Brewing unit	7 gr or 9 gr
Available cups ø	70 or 73 mm
Available stirrers	90 - 105 - 115 mm
Number of selections	8
Number of preselections	up to 4

Capacities	Rubino 200
Coffee beans	2.0 kg
Instant coffee	0.7 kg
Milk	0.85 kg
Chocolate	1.7 kg
Tea	2.35 kg
Sugar	2.0 kg
Cups (h 70 mm)	195
Stirrers	180
Independent water tank	20 l

#### Technical specifications

- Pre-galvanized and painted steel-sheet body
- Thermoplastic door
- Thermoplastic cover with transparent coffee bean container
- Containers and tanks in food-contact approved polypropylene
- Water, coffee and cup-empty signal
- Software function setting the maximum number of coffee cycles permitted before the dump box is removed and emptied
- Electronically controlled boiler temperature
- Exhauster to absorb internal moisture and additional steam exhauster for the dispensing area
- Removable cup-releasing device for easy cleaning and checking
- 60 W electromagnetic vibration pump
- Anti-overflow air-break device
- Simplified error reset
- Boiler safety valve
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- CE, VDE and UL approved

#### User interface

- Direct access 8-button keypad for beverage selection
- 2 keys for sugar preselection
- Option to set 2 preselection keys: one for decaffeinated/barley and one for no-cup option
- 2-line, 20-character alphanumeric display



### Saeco Vending S.p.A.

Località Casona, 1066  
40041 Gaggio Montano, Bologna - Italy  
Tel: +39 0534 7741 - Fax: +39 0534 774808

info.saecovending@saeco.com  
www.saeco.com

Always at your service:

