

Smeraldo 36/56

Smeraldo 36 and 56 are spiral vending machines equipped with 5 and 6 removable trays for dispensing 36 to 56 different products. The machines guarantee a minimum internal temperature of 8°C at a room temperature of 32°C.

They are perfectly co-ordinated with Quarzo 500/700 and Cristallo 400/600.



Main features

- Accepts the most commonly used parallel and serial MDB, BDV and Executive (possible Master and Slave configurations) payment systems
- Personalisation of the spiral and tray configuration
- High safety for customer and operator

Accessories

- Timekeeper kit
- Pre-perforated modules kit for the main payment systems
- 12 V DC validator kit
- Photocell kit
- Memory key to copy and quickly transfer machine settings
- Eva-Dts kit



Technical Data	Smeraldo 36	Smeraldo 56
Dimensions (w x h x d)	700 x 1700 x 850 mm	850 x 1830 x 862 mm
Weight	222 kg	260 kg
Power supply	230 V/50 Hz	230 V/50 Hz 120 V/60 Hz
Power consumption	600 W	700 W
Refrigerating unit	1/5 HP	1/4 HP
Adjustable temperature	6°C-15°C	6°C-15°C
Ecological refrigerant fluid	R 404a	R 404a

Capacities	Smeraldo 36	Smeraldo 56
Number of trays	5-6	6-7
Bottle tray	36 bottles Ø 69 mm, h 210 mm	48 bottles Ø 69 mm, h 210 mm
Can tray	36 cans	48 cans
Snack tray	according to the spiral type	according to the spiral type
Number of spirals	30-36	48-56
Available spirals	17 (27 products) to 90 (5 products) pitch	17 (27 products) to 90 (5 products) pitch

Technical specifications

- Painted steel-sheet body with expanded polyurethane insulation
- Double-layer safety glass with insulation cushion
- Product dispensing slot: swinging and counterbalanced for easy opening, equipped with anti-theft system
- Removable plastic trays, which provide a suitable resistance to weight. The tray position can easily be adjusted with 30 mm shifts
- Self configuration with automatic reset at every machine start
- Programming temperature and sale prices (up to 25)
- Illumination with fluorescent lamp
- Anti-frost probe: automatic defrost cycles
- Simple failure reset
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- CE and VDE approved

User interface

- 9-button keypad
- 2-line, 16-character alphanumeric display




Mixed Sources
 Product group from well-managed forests
 and other controlled sources
www.fsc.org Zert.-Nr. GFA-COC-001492
 © 1996 Forest Stewardship Council

Saeco Vending S.p.A.

Località Casona, 1066
 40041 Gaggio Montano, Bologna - Italy
 Tel: +39 0534 7741 - Fax: +39 0534 774808

info.saecovending@saeco.com
www.saeco.com

Always at your service: