

Zaffiro 300

Technologically innovative and extremely easy to use and maintain, Zaffiro 300 is a completely automatic table-top vending machine designed for small and medium locations and offices.

Available with cabinet, in the Espresso and Instant versions, it offers up to 8 different beverages.



Main features

- Automatically dispenses cups (up to 280), sugar and stirrers
- Saeco Brewing Unit (Espresso version): top quality espresso, easy cleaning and maintenance
- Accepts the most commonly used parallel and serial MDB, BDV and Executive (possible Master and Slave configurations) payment systems
- Coffee preheater (Instant version)
- Customisable settings
- High safety for customer and operator
- Independent water tank kit
- Timekeeper kit
- Mixer kit for tea spiral replacement with decaffeinated/ barley
- Hot water solenoid valve kit (Espresso version)
- Neon light kit
- Pre-perforated modules for various payment systems
- Power supply kit for additional payment systems
- Table-top assembly kit
- Kit for discharge fluid level control
- Electromechanical pulse counter kit
- Memory key to copy and quickly transfer machine settings
- Eva-Dts kit

Accessories

- Cabinet with height-adjustable feet (w x h x d 520 x 836 x 560 mm, 28 kg)

Ideas with Passion

 **Saeco**



Technical Data	Zaffiro 300 Espresso	Zaffiro 300 Instant
Dimensions (w x h x d)	520 x 810 x 560 mm	520 x 810 x 560 mm
Weight	60 kg	57 kg
Power supply	230 V/50 Hz 120 V/60 Hz	230 V/50 Hz 120 V/60 Hz
Power consumption	1250 W	1350 W
Boiler	brass	brass
Water connection	3/4" (1-8 bar)	3/4" (1-8 bar)
Water supply	standard: water supply optional: independent water tank kit	standard: water supply optional: independent water tank kit
Coffee bean container	1	-
Instant product container	3	4
Sugar container	1	1
Disc mixer	2	3
Spiral mixer	1	1
Brewing unit	7 gr or 9 gr	-
Available cups ø	70 or 73 mm	70 or 73 mm
Available stirrers	90 - 105 - 115 mm	90 - 105 - 115 mm
Number of selections	8	8
Number of preselections	4	4

Capacities	Zaffiro 300 Espresso	Zaffiro 300 Instant
Coffee beans	3.8 kg	-
Instant coffee	-	0.5 kg
Milk	1.2 kg	1.2 kg
Chocolate	2.5 kg	2.5 kg
Tea	2.0 kg	2.0 kg
Sugar	2.0 kg	2.0 kg
Cups (h 70 mm)	280	280
Stirrers	280	280
Independent water tank	20 l	20 l

Technical specifications

- Pre-galvanized and painted steel-sheet body
- Thermoplastic door
- Containers and tanks in food-contact approved resin
- Water, coffee and cup-empty signal
- Software function setting the maximum number of coffee cycles permitted before the dump box is removed and emptied
- Electronically controlled boiler temperature
- Exhauster to absorb internal moisture and additional steam exhauster for the dispensing area
- 60 W electromagnetic vibration pump
- Anti-overflow air-break device
- RS 232 serial port for programming and statistical data gathering
- Built-in utility outlet
- Boiler safety valve
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- CE, VDE and UL approved

User interface

- Direct access 8-button keypad for beverage selection
- 4 preselection keys: +/- sugar, decaffeinated/barley and no-cup option
- 2-line, 20-character alphanumeric display



Saeco Vending S.p.A.

Località Casona, 1066
40041 Gaggio Montano, Bologna - Italy
Tel: +39 0534 7741 - Fax: +39 0534 774808

info.saecovending@saeco.com
www.saeco.com

Always at your service: